SIGMA



Anodized aluminium 6060 extruded profile, designed and produced to be recess-mounted also on very small surfaces. Extremely easy to install, thanks to the brushed snap-in diffuser and side supports. Ideal to house and dissipate LED Strips, and especially suited to illuminate and embellish kitchens, under-wall cupboards, furniture, closets, shelves and plasterboard.


EXTRUDED IN ITALY





56 www.nanoledlighting.com





BASIC CODES

LENGTH

FINISHES




PA.SIGMA.

1 1000mm
2 2000mm

1 Matt white RAL9003

2 Matt black RAL9005





BASIC CODES

SG01.

FINISHES


IIVIOIILO

_ 1 White

2 Matt black5 Grey

7 Brushed aluminium

Side closing support and ABS flush-mounting, Easy and quick to install, by exerting a slight side pressure.



BASIC CODES

LENGTH


PA.13PE49.

1 1000mm brushed

2 2000mm brushed

3 3000mm brushed

Brushed snap-on diffuser. The diffuser can be easily removed for maintenance operations.




BASIC CODES

PA.GG06

Steel fixing clips for flush-mounting on wood or plasterboard.

NB. We recommend No. 1 Clip per 500mm



BASIC CODES

TC02

Rectangular electronic device with ON/OFF TOUCH system. The LED can be switched ON/OFF by gently touching the sensitive device section. To be installed inside the profile, in contact with the diffuser, with the double-sided tape supplied (12Vdc and 24Vdc 4A max.)

 $\label{eq:code_constraints} \textbf{Code example: SIGMA Profile} + 1000 mm \ \textbf{Length} + \textbf{Brushed Aluminium Finish} = \textbf{Code: PA.SIGMA.17}$

www.nanoledlighting.com 57