



Polycarbonate lamp complete with aluminium heat sink and high-brightness LED source with a high Lumen/Watt ratio. Suitable for accent lighting of furnishing, retail and general lighting.

Constant 24Vdc voltage supply Parallel connection, 50 cm cable

Constant voltage power supplies page 237 Dimming Accessories page 249





BASIC CODES	SIZE	LED COLOUR	POWER
Q1.	<b>A</b> 300mm	■ BN 4000K	0+ 12W/m 1000Lm/m 300LED/m S2216 CRI>90 F
	<b>B</b> 450mm	■ <b>BC</b> 3000K	
	<b>C</b> 500mm	<b>□ CC</b> 2700K	P+ 14.4W/m 1100Lm/m 180LED/m S2216 CRI>90 G
	<b>D</b> 600mm		*Energy class referring to light source
	<b>E</b> 700mm		3,
	<b>F</b> 800mm		
	<b>G</b> 900mm		
	<b>H</b> 1000mm		
	l 1200mm		
	<b>J</b> 1300mm		
	<b>K</b> 1400mm		
	<b>L</b> 1500mm		
	<b>M</b> 1800mm		
	<b>N</b> 2000mm		
	<b>0</b> 2300mm		
	<b>P</b> 2500mm		
	<b>Q</b> 2800mm		
	<b>R</b> 3000mm		

Code example:

QU + 1000mm + 3000K + 12W/m CRI>90 = Code: Q1.HBCO+

## ACCESSORIES TO BE ORDERED SEPARATELY

BASIC CODES WIDTH BASIC CODES WIDTH

NM. 4965. 08 8 mm



Magnetic adhesive tape for anodised aluminium profiles. Supplied on a 10-metre reel, 1.2 mm thickness. (Force of attraction >40g/cm².)

Double-sided adhesive tape for aluminium profiles and LED strips. Supplied on a 50-metre reel.

www.nanoledlighting.com 171