

# VELA 2

V2.






Decorated anodised aluminium lamp complete with press-fit brushed diffuser , side supports and LED source with a high Lumen/Watt ratio. Wide availability of accessories that can be integrated into the profile. Suitable for primary residential and general lighting. Mounting with recessed clips.

Constant 24Vdc voltage supply  
Parallel connection, 50 cm cable

Constant voltage power supplies page 237  
Dimming Accessories page 249

 **MADE IN ITALY**



BASIC CODES

**V2.**

FINISHES

- 1** White
  - 2** Matt black
  - 7** Brushed aluminium
- \*Other finishes on request.

SIDE SUPPORTS

- 1** White
- 2** Matt black
- 7** Brushed aluminium

SIDE SUPPORTS + TOUCH

- 1T** White
- 2T** Matt black
- 7T** Brushed aluminium

SIDE SUPPORTS + SENSOR

- 1S** White
- 2S** Matt black
- 7S** Brushed aluminium

SIZE

- A** 300mm
- B** 450mm
- C** 500mm
- D** 600mm
- E** 700mm
- F** 800mm
- G** 900mm
- H** 1000mm
- I** 1200mm
- J** 1300mm
- K** 1400mm
- L** 1500mm
- M** 1800mm
- N** 2000mm
- O** 2300mm
- P** 2500mm
- Q** 2800mm
- R** 3000mm

LED COLOUR

- BN** 4000K
  - BC** 3000K
  - CC** 2700K
- \*Strip also available coloured, Dynamic White, RGB and RGBW.

POWER

- |           |         |          |          |       |        |   |
|-----------|---------|----------|----------|-------|--------|---|
| <b>E</b>  | 16.8W/m | 2000Lm/m | 140LED/m | S2835 | CRI>85 |  |
| <b>E+</b> | 16.8W/m | 2000Lm/m | 140LED/m | S2835 | CRI>90 |  |
| <b>F</b>  | 20.2W/m | 2500Lm/m | 168LED/m | S2835 | CRI>85 |  |
| <b>F+</b> | 20.2W/m | 2500Lm/m | 168LED/m | S2835 | CRI>90 |  |
| <b>G</b>  | 25W/m   | 3500Lm/m | 160LED/m | S2835 | CRI>80 |  |
| <b>L+</b> | 28W/m   | 3500Lm/m | 160LED/m | S2835 | CRI>90 |  |
| <b>H</b>  | 30W/m   | 4500Lm/m | 240LED/m | S2835 | CRI>80 |  |

\*Energy class referring to light source

DIFFUSER

- S** BRUSHED

Code example:

VELA 2 + White + Side supports white + 1000mm + 3000K + 25W/m CRI>80 + Brushed diffuser = Code: V2.11HBCGS